
Meridian 1

Electronic Switched Network

Signaling guidelines

Document Number: 309-3001-180

Document Release: Standard 3.0

Date: December 1994

© 1982, 1994

All rights reserved

Printed in the United States of America

Information is subject to change without notice. Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

Revision history

August 10, 1990

Standard, release 1.0. Reissued for compliance with Northern Telecom standard 164.0.

December 1, 1991

Standard, release 2.0. This document is reissued to include technical content updates. Because of the extent of the changes, revision bars are omitted.

December 1994

Standard, release 3.0. Reissued to include editorial changes and indexing. Due to the extent of the changes, revision bars are not used.

Contents

Introduction	1
PBX networks	1
PBX designations	2
Node switch	2
Main switch	3
Tributary switch	3
Satellite switch	3
CCSA tandem switch	3
Supervision	4
Digit transmission	5
Modes of operation	5
Cut-through mode	6
DTMF to DP conversion	6
Senderized mode	7
Outpulsing control	7
Immediate start	7
Delay for dial tone	7
Wink start	7
Delay dial	8
Call setup sequences in ESN	9
Calls to the node	9
Case 1	9
Case 2	10
Case 3	10
Case 4	11

Case 5	11
Case 6	11
Call completions	12
Case 1	13
Case 2	13
Case 3	13
Case 4	14
Calls to other private networks	14
Tandem tie trunk networks (TTTN)	14
Common control switching arrangement (CCSA)	14
Calls from other private networks	15
Requirements for dialing pauses	15